

Emanuele Ricci, 2023



Suspension lamp providing direct and diffused light. The glass diffuser consists of 6 sheets of 15 mm thick extra-clear float glass, glued together, milled, ground and polished to a perfect quality shape. The mount housing the customized integrated LED is machined from aluminum billet using a CNC machine. The mount is finished in brushed nickel or brushed gold.

FINISHINGS

<p>Brushed Nickel 3000K - cod. GALD44K30 2700K - cod. GALD44K27 ON/OFF-PUSH DIM-1/10V DALI Ceiling rose: Brushed Nickel/Black</p>	<p>Brushed Gold 3000K - cod. GALD45K30 2700K - cod. GALD45K27 ON/OFF-PUSH DIM-1/10V DALI Ceiling rose: Brushed Gold/Black</p>
<p>Brushed Nickel 3000K - cod. GALT44K30220 2700K - cod. GALT44K27220 PHASE CUT Ceiling rose: Brushed Nickel/Black</p>	<p>Brushed Gold 3000K - cod. GALT45K30220 2700K - cod. GALT45K27220 PHASE CUT Ceiling rose: Brushed Gold/Black</p>

LIGHT EMISSION

Light source power: 12W	Efficacy 3000K: 45 lm/W
Power absorption: 18W	Source Flux 2700K: 1360lm@350mA
Light Emission: Diffuse	Emitted Flux 2700K: 641 lm
Light Direction: Directional	Efficacy 2700K: 43 lm/W
Light Source: COB LED	CCT: 2700/3000K
Source Flux 3000K: 1400lm@350mA	CRI: 97
Emitted Flux 3000K: 692 lm	Lifetime: >55000h

ELECTRICAL FACTS

Stand-by absorption: < 0,5
Mains Voltage: 100-264VAC
Master output: 350mA
Ta max: 40°C

PACKAGING DATA

Box dimensions: 29,5x28,7x26,8cm
Volume: 0,023 m³
Gross weight: 5 kg

