

Jean-Michel Wilmotte, 2023



The main body is made of a turned aluminum body housing a LED engine with dedicated optics. Opaline glass, diffuses and reflects soft and comfortable light. The outer frame is composed by 4 elements made in photo-etched stainless steel. Brushed stainless-steel stem shows and houses the colored fabric power cable. Base in transparent glass

FINISHINGS

<p>Matt Black 3000K - cod. ANM010PK30 2700K - cod. ANM010PK27</p> <p>Matt White 3000K - cod. ANM020PK30 2700K - cod. ANM020PK27</p> <p>Anodised Brass 3000K - cod. ANM50XOK30 2700K - cod. ANM50XOK27</p> <p>Anodised Blue 3000K - cod. ANM51XOK30 2700K - cod. ANM51XOK27</p>	<p>Gun Metal 3000K - cod. ANM32K30 2700K - cod. ANM32K27</p>
--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	-----------------------------------------------------------------------------

ALL RAL COATING AND GALVANIC FINISHES AVAILABLE UPON REQUEST

LIGHT EMISSION

Light source power: 8,75W	Efficacy 3000K: 43 lm/W
Power absorption: 11,4W	Source Flux 2700K: 750lm@700mA
Light Emission: Diffuse	Emitted Flux 2700K: 462lm
Light Direction: Downlight	Efficacy 2700K: 41 lm/W
Light Source: Discrete LED	CCT: 2700/3000K
Source Flux 3000K: 792lm@700mA	CRI: 97
Emitted Flux 3000K: 488 lm	Lifetime: >55000h

ELECTRICAL FACTS

Stand-by absorption: <0.6
Mains Voltage: 100/264VAC
Master output: 700mA
Ta max: 40°C

PACKAGING DATA

Box dimensions: 43x43x23 cm
Volume: 0,04 m ³
Gross weight: 6,3 kg

